

Actuator

45-2131.4F10.000











45-2131.4F10.000 Actuator

_	_	_		-
-	к	u	N	

Front dimension: Ø 38 mm

Front form: Round

Front bezel colour: Sand grey

Front bezel material: Metal

MOUNTING

Design: Flush

Mounting cut-out: Ø 30.5 mm

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lens colour: Black

Lens material: Plastic

Lens illumination: Non illuminated

Lens shape: Flush

Lens optics: opaque

MECHANICAL CHARACTERISTICS

Switching action: Momentary

Switching system: Slow-make switching element

Mechanical lifetime: 500 000 cycles of operation

Operating frequency: Max. 3 600/h

AMBIENT CONDITION IP front protection: IP66, IP67, IP69K Operating temperature: - 25 °C + 70 °C Storage temperature: - 40 °C + 80 °C Shock resistance: According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms Vibration resistance: According to IEC 60068-2-6: 20 500 Hz: 5 g Climate resistance: During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6 CERTIFICATE REACH: REACH: REACH compliant OTHER Short Description: Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K Housing colour: Housing material: Metal Hints: Front panel thickness 1 6 mm Wiring diagrams:			
Operating temperature: - 25 °C + 70 °C Storage temperature: - 40 °C + 80 °C Shock resistance: According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms Vibration resistance: According to IEC 60068-2-6: 20 500 Hz: 5 g Climate resistance: During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6 CERTIFICATE REACH: REACH: ROHS: ROHS compliant OTHER Short Description: Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K Housing colour: Housing material: Metal Hints: Front panel thickness 1 6 mm	AMBIENT CONDITION		
Storage temperature: - 40 °C + 80 °C Shock resistance: According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms Vibration resistance: According to IEC 60068-2-6: 20 500 Hz: 5 g Climate resistance: During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6 CERTIFICATE REACH: REACH: REACH compliant RoHS: RoHS compliant OTHER Short Description: Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K Housing colour: Housing material: Metal Hints: Front panel thickness 1 6 mm	IP front protection:	IP66, IP67, IP69K	
Shock resistance: According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms Vibration resistance: According to IEC 60068-2-6: 20 500 Hz: 5 g Climate resistance: During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6 CERTIFICATE REACH: REACH: REACH compliant RoHS: ROHS compliant OTHER Short Description: Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K Housing colour: Housing material: Metal Hints: Front panel thickness 1 6 mm	Operating temperature:	– 25 °C + 70 °C	
Vibration resistance: According to IEC 60068-2-6: 20 500 Hz: 5 g Climate resistance: During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6 CERTIFICATE REACH: REACH compliant RoHS: RoHS compliant OTHER Short Description: Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K Housing colour: Silver Housing material: Metal Hints: Front panel thickness 1 6 mm	Storage temperature:	– 40 °C + 80 °C	
Climate resistance: During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6 CERTIFICATE REACH: REACH: REACH compliant RoHS: ROHS compliant OTHER Short Description: Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K Housing colour: Silver Housing material: Metal Hints: Front panel thickness 1 6 mm	Shock resistance:	According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms	
CERTIFICATE REACH: REACH compliant RoHS: RoHS compliant OTHER Short Description: Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K Housing colour: Silver Housing material: Metal Hints: Front panel thickness 1 6 mm	Vibration resistance:	According to IEC 60068-2-6: 20 500 Hz: 5 g	
REACH: REACH compliant RoHS: RoHS compliant OTHER Short Description: Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K Housing colour: Silver Housing material: Metal Hints: Front panel thickness 1 6 mm	Climate resistance:	During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6	
REACH: REACH compliant RoHS: RoHS compliant OTHER Short Description: Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K Housing colour: Silver Housing material: Metal Hints: Front panel thickness 1 6 mm			
RoHS: RoHS compliant OTHER Short Description: Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K Housing colour: Silver Housing material: Metal Hints: Front panel thickness 1 6 mm	CERTIFICATE		
OTHER Short Description: Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K Housing colour: Housing material: Metal Front panel thickness 1 6 mm	REACH:	REACH compliant	
Short Description: Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K Housing colour: Silver Housing material: Metal Hints: Front panel thickness 1 6 mm	RoHS:	RoHS compliant	
Short Description: Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K Housing colour: Silver Housing material: Metal Hints: Front panel thickness 1 6 mm			
Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K Housing colour: Silver Housing material: Metal Hints: Front panel thickness 1 6 mm	OTHER		
Housing material: Metal Hints: Front panel thickness 1 6 mm	Short Description:	Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Black, Plastic, opaque, Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K	
Hints: Front panel thickness 1 6 mm	Housing colour:	Silver	
	Housing material:	Metal	
Wiring diagrams:	Hints:	Front panel thickness 1 6 mm	
Dimension drawings:		_	

0.074 kg

Weight:

