

Actuator

45-2131.4F20.000











45-2131.4F20.000 Actuator

Е	D	0	N	٦
г	п	v	14	

Front dimension: Ø 38 mm

Front form: Round

Front bezel colour: Sand grey

Front bezel material: Metal

MOUNTING

Design: Flush

Mounting cut-out: Ø 30.5 mm

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lens colour: Red

Lens material: Plastic

Lens illumination: Non illuminated

Lens shape: Flush

Lens optics: opaque

MECHANICAL CHARACTERISTICS

Switching action: Momentary

Switching system: Slow-make switching element

Mechanical lifetime: 500 000 cycles of operation

Operating frequency: Max. 3 600/h

AMBIENT CONDITION		
IP front protection:	IP66, IP67, IP69K	
Operating temperature:	– 25 °C + 70 °C	
Storage temperature:	– 40 °C + 80 °C	
Shock resistance:	According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms	
Vibration resistance:	According to IEC 60068-2-6: 20 500 Hz: 5 g	
Climate resistance:	During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6	
CERTIFICATE		
REACH:	REACH compliant	
RoHS:	RoHS compliant	
OTHER		
Short Description:	Actuator, Ø 30.5 mm, Ø 38 mm, Flush, Non illuminated, Red, Plastic, opaque, Round, Sand grey, Metal, Momentary, IP66, IP67, IP69K	
Housing colour:	Silver	
Housing material:	Metal	
Hints:	Front panel thickness 1 6 mm	
Wiring diagrams:	E	
Dimension drawings:		

0.074 kg

Weight:

