

# Actuator

45-2134.2120.000











## 45-2134.2120.000 Actuator

_	_	_		-
-	к	u	N	

Front dimension: Ø 29,5 mm
Front form: Round

Silver

Front bezel material: Metal

## MOUNTING

Front bezel colour:

Design: Raised

Mounting cut-out: Ø 22.3 mm

Mounting type: Panel mounting

#### **OPERATING-/INDICATION PART**

Lens colour: Red

Lens material: Plastic

Lens illumination: Non illuminated

Lens shape: Flush

Lens optics: opaque

**Lens type:** Level with front bezel


## **MECHANICAL CHARACTERISTICS**

Switching action: Maintained

Switching system: Slow-make switching element

**Mechanical lifetime:** 10 Mil. cycles of operation

Weight:	0.036 kg		
AMBIENT CONDITION			
IP front protection:	IP66, IP67, IP69K		
Operating temperature:	– 25 °C + 70 °C		
Storage temperature:	– 40 °C + 80 °C		
Shock resistance:	According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms		
Vibration resistance:	According to IEC 60068-2-6: 20 500 Hz: 5 g		
Climate resistance:	During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6		
CERTIFICATE			
REACH:	REACH compliant		
RoHS:	RoHS compliant		
OTHER			
Short Description:	Actuator, Ø 22.3 mm, Ø 29,5 mm, Flush, Non illuminated, Red, Plastic, opaque, Round, Silver, Metal, Maintained, IP66, IP67, IP69K		
Housing colour:	Silver		
Housing material:	Metal		
Hints:	Push to unlatch		
Wiring diagrams:			
	_~-		
Mounting cut-outs:			



## Dimension drawings:

