

Your Expert Partner for Human Machine Interfaces

Actuator



45-2231.12E0.000

Риминя крытану, штамина каки притику каракан и пичаск зрзачи, п**,** гарыч,



Your product:



45-2231.12E0.000 Actuator

_	_	_		-
-	к	u	N	

Front dimension: ∅ 29,5 mm

Front form: Round

Front bezel colour: Black

Front bezel material: Plastic

MOUNTING

Design: Raised

Mounting cut-out: Ø 22.3 mm

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lens colour: Red

Lens material: Plastic

Lens illumination: Illuminated

Lens shape: Flush

Lens optics: transparent

Lens type: Raised above front bezel

Illumination colour: Red

MECHANICAL CHARACTERISTICS

Switching action: Momentary

Switching system: Slow-make switching element

Mechanical lifetime:	3 Mil. cycles of operation	
Operating frequency:	Max. 3 600/h	
Weight:	0.019 kg	
AMBIENT CONDITION		
IP front protection:	IP66, IP67, IP69K	
Operating temperature:	– 25 °C + 70 °C	
Storage temperature:	– 40 °C + 80 °C	
Shock resistance:	According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms	
Vibration resistance:	According to IEC 60068-2-6: 20 500 Hz: 5 g	
Climate resistance:	During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6	
CERTIFICATE		
REACH:	REACH compliant	
RoHS:	RoHS compliant	
OTHER		
Short Description:	Actuator, \varnothing 22.3 mm, \varnothing 29,5 mm, Flush, Illuminated, Red, Plastic, transparent, Round, Black, Plastic, Momentary, IP66, IP67, IP69K, Red	
Housing colour:	Black	
Housing material:	Plastic	
Wiring diagrams:	Wiring diagrams	
Mounting cut-outs:		
	Mounting cut-outs	
Dimension drawings:		

