

Actuator

45-

2530.1920.000







Your product:



45-2530.1920.000 Actuator

FRONT

Front dimension: Ø 40 mm

Front form: Round

Front bezel colour: Black

Front bezel material: Plastic

MOUNTING

Design: Raised

Mounting cut-out: Ø 22.3 mm

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lens colour: Red

Lens material: Plastic

Lens illumination: Non illuminated

Lens shape: Mushroom-head

Lens optics: opaque

MECHANICAL CHARACTERISTICS


Switching action: Maintained

Switching system: Slow-make switching element

Release type: Pull unlock

Mechanical lifetime: 500 000 cycles of operation

Operating frequency:	Max. 1 800/h
Weight:	0.028 kg
AMBIENT CONDITION	
IP front protection:	IP66, IP67, IP69K
Operating temperature:	– 25 °C + 70 °C
Storage temperature:	– 40 °C + 80 °C
Shock resistance:	According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms
Vibration resistance:	According to IEC 60068-2-6: 20 500 Hz: 5 g
Climate resistance:	During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6
CERTIFICATE	
REACH:	REACH compliant
RoHS:	RoHS compliant
OTHER	
Short Description:	Actuator, Ø 22.3 mm, Ø 40 mm, Mushroom-head, Non illuminated, Red, Plastic, opaque, Round, Black, Plastic, Maintained, IP66, IP67, IP69K, Pull unlock
Housing colour:	Black
Housing material:	Plastic
Wiring diagrams:	
	_~-
Mounting cut-outs:	



Dimension drawings:

