

# Actuator

45-

290K.1000.116









## 45-290K.1000.116 Actuator

### **FRONT**

Front dimension: Ø 29,5 mm

Front form: Round

Front bezel colour: Black

Front bezel material: Plastic

#### **MOUNTING**

Design: Raised

Mounting cut-out: Ø 22.3 mm

Mounting type: Panel mounting

#### **MECHANICAL CHARACTERISTICS**

**Switching action:** Rest (a) - Momentary

**Switching positions:** 2 positions

**Switching angle:** 45° right

**Mechanical lifetime:** 1 Mil. cycles of operation

Operating frequency: 1 800/h

**Weight:** 0.054 kg

## AMBIENT CONDITION

**IP front protection:** IP66, IP67, IP69K

**Operating temperature:**  $-25 \, ^{\circ}\text{C} \, ... + 70 \, ^{\circ}\text{C}$ 

Storage temperature:  $-40 \, ^{\circ}\text{C} \dots + 80 \, ^{\circ}\text{C}$ 

**Shock resistance:** According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms

**Vibration resistance:** According to IEC 60068-2-6: 10 ... 500 Hz: 5 g

Climate resistance: During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6

**CERTIFICATE** 

**REACH:** REACH compliant

RoHS: RoHS compliant

**OTHER** 


Short Description: Actuator, Ø 22.3 mm, Ø 29,5 mm, Round, Black, Plastic, Rest (a) - Momentary,

IP66, IP67, IP69K

Housing material: Plastic

**Hints:** The standard lock: RONIS, T254


Switching positions:



Wiring diagrams:



Mounting cut-outs:



## Dimension drawings:

