

Actuator

45-2C35.1920.110











45-2C35.1920.110 Actuator

Е	D	0	N	٦
г	п	v	14	

Front dimension: Ø 40 mm

Front form: Round

Front bezel colour: Black

Front bezel material: Plastic

MOUNTING

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lens colour: Red

Lens material: Plastic

Lens illumination: Non illuminated

Lens shape: Mushroom-head

Lens optics: opaque

MECHANICAL CHARACTERISTICS

Switching action: Maintained

Release type: Key release to unlock


Mechanical lifetime: 300 000 cycles of operation

Operating frequency: Max. 600/h

Weight: 0.075 kg

AMBIENT CONDITION

Operating temperature:	– 25 °C + 70 °C	
Storage temperature:	– 40 °C + 80 °C	
Shock resistance:	According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms	
Vibration resistance:	According to IEC 60068-2-6: 2 500 Hz: 5 g	
Climate resistance:	During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6	
CERTIFICATE		
REACH:	REACH compliant	
RoHS:	RoHS compliant	
OTHER		
Short Description:	Actuator, \varnothing 40 mm, Mushroom-head, Non illuminated, Red, Plastic, opaque, Round, Black, Plastic, Maintained, Key release to unlock	
Dimension:	Ø 40 mm	
Housing colour:	Yellow	
Housing material:	Plastic	
Product attributes:	Key release to unlock anti-clockwise	
Hints:	Application as per DIN EN ISO 13850 and EN 60204-1	
Wiring diagrams:	0-8-~-	
Mounting cut-outs:		



Dimension drawings:

