

Actuator

45-2C36.1920.000









Your product:



45-2C36.1920.000 Actuator

| | _ | _ | | - |
|----|---|----|---|---|
| ь. | к | () | N | |
| | | | | |

Front dimension: Ø 40 mm

Front form: Round

Front bezel colour: Black

Front bezel material: Plastic

MOUNTING

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lens colour: Red

Lens material: Plastic

Lens illumination: Non illuminated

Lens shape: Mushroom-head

Lens optics: opaque

MECHANICAL CHARACTERISTICS

Switching action: Maintained

Release type: Twist to unlock


Mechanical lifetime: 300 000 cycles of operation

Operating frequency: Max. 600/h

Weight: 0.045 kg

AMBIENT CONDITION

| Operating temperature: | – 25 °C + 70 °C | | |
|------------------------|---|--|--|
| Storage temperature: | – 40 °C + 80 °C | | |
| Shock resistance: | According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms | | |
| Vibration resistance: | According to IEC 60068-2-6: 2 500 Hz: 5 g | | |
| Climate resistance: | During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6 | | |
| | | | |
| CERTIFICATE | | | |
| REACH: | REACH compliant | | |
| RoHS: | RoHS compliant | | |
| | | | |
| OTHER | | | |
| Short Description: | Actuator, Ø 40 mm, Mushroom-head, Non illuminated, Red, Plastic, opaque, Round, Black, Plastic, Maintained, Twist to unlock | | |
| Dimension: | Ø 40 mm | | |
| Housing colour: | Yellow | | |
| Housing material: | Plastic | | |
| Product attributes: | Twist to unlock clockwise | | |
| Hints: | Application as per DIN EN ISO 13850 and EN 60204-1 | | |
| Wiring diagrams: | | | |
| | <u></u> | | |
| Mounting cut-outs: | | | |



Dimension drawings:

