

Actuator

45-2C36.1A20.000









Your product:



45-2C36.1A20.000 Actuator

FRONT

Front dimension: Ø 60 mm

Front form: Round

Front bezel colour: Black

Front bezel material: Plastic

MOUNTING

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lens colour: Red

Lens material: Plastic

Lens illumination: Non illuminated

Lens shape: Mushroom-head

Lens optics: opaque

MECHANICAL CHARACTERISTICS

Switching action: Maintained

Release type: Twist to unlock


Mechanical lifetime: 300 000 cycles of operation

Operating frequency: Max. 600/h

Weight: 0.066 kg

AMBIENT CONDITION

Operating temperature:	– 25 °C + 70 °C
Storage temperature:	– 40 °C + 80 °C
Shock resistance:	According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms
Vibration resistance:	According to IEC 60068-2-6: 2 500 Hz: 5 g
Climate resistance:	During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6
CERTIFICATE	
REACH:	REACH compliant
RoHS:	RoHS compliant
OTHER	
Short Description:	Actuator, \emptyset 60 mm, Mushroom-head, Non illuminated, Red, Plastic, opaque, Round, Black, Plastic, Maintained, Twist to unlock
Dimension:	Ø 60 mm
Housing colour:	Yellow
Housing material:	Plastic
Product attributes:	Twist to unlock clockwise
Hints:	Application as per DIN EN ISO 13850 and EN 60204-1
Wiring diagrams:	<u></u>
Mounting cut-outs:	



Dimension drawings:

