

Actuator

45-2D36.1820.000









Your product:



45-2D36.1820.000 Actuator

		\sim		_
-	к	()	N	
		v		

Front dimension: Ø 34 mm

Front form: Round

Front bezel colour: Black

Front bezel material: Plastic

MOUNTING

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lens colour: Red

Lens material: Plastic

Lens illumination: Illuminated

Lens shape: Mushroom-head

Lens optics: opaque

MECHANICAL CHARACTERISTICS

Switching action: Maintained

Release type: Twist to unlock

Mechanical lifetime: 300 000 cycles of operation

Operating frequency: Max. 600/h

Weight: 0.042 kg

AMBIENT CONDITION

Operating temperature: $-25 \, ^{\circ}\text{C} \, ... + 70 \, ^{\circ}\text{C}$

Storage temperature: $-40 \, ^{\circ}\text{C} \dots + 80 \, ^{\circ}\text{C}$

Shock resistance: According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms

Vibration resistance: According to IEC 60068-2-6: 2 ... 500 Hz: 5 g

Climate resistance: During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6

CERTIFICATE

REACH: REACH compliant

RoHS: RoHS compliant

OTHER

Short Description: Actuator, Ø 34 mm, Mushroom-head, Illuminated, Red, Plastic, opaque, Round,

Black, Plastic, Maintained, Twist to unlock

Dimension: Ø 34 mm


Housing colour: Yellow

Housing material: Plastic


Product attributes: Twist to unlock anti-clockwise

Hints: Application as per DIN EN ISO 13850 and EN 60204-1

Wiring diagrams:



Mounting cut-outs:



Dimension drawings:

