

Actuator

45-
482.1810

Distribution by
Newark



[https://newark.eao.com/component/45-482.1810/...](https://newark.eao.com/component/45-482.1810/)

Your product:



45-482.1810
Actuator

FRONT

Front dimension:	85 mm x 85 mm
Front form:	Square

MOUNTING

Design:	Raised
Mounting cut-out:	Ø 22.3 mm
Component mounting type:	Base mounting
Mounting type:	Panel mounting

OPERATING-/INDICATION PART

Lens colour:	Red
Lens material:	Plastic
Lens illumination:	Non illuminated
Lens optics:	opaque

ELECTRICAL CHARACTERISTICS

Rated Operational Voltage Ue:	At AC: rated value 5 ... 500 V At DC: rated value 5 ... 500 V
--------------------------------------	--

MECHANICAL CHARACTERISTICS

Switching action:	Maintained
Switching system:	Slow-make switching element
Release type:	Pull unlock

Weight: 0.414 kg

AMBIENT CONDITION

IP front protection: IP66, IP67, IP69K

Storage temperature: - 40 °C ... + 80 °C

Shock resistance: According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms

Vibration resistance: According to IEC 60068-2-6: 10 ... 500 Hz: 5 g

Climate resistance: During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6, 3B2

CERTIFICATE

REACH: REACH compliant

RoHS: RoHS compliant

OTHER

Short Description: Actuator, Ø 22.3 mm, 85 mm x 85 mm, Non illuminated, Red, Plastic, opaque, Square, Maintained, IP66, IP67, IP69K, Pull unlock

Housing colour: Yellow

Housing material: Plastic

Product attributes: Pull release

Dimension drawings:

