

Actuator

46-

2W0S.1CN0.004









https://newark.eao.com/component/46-2W0S.1CN0...



46-2W0S.1CN0.004 Actuator

Front dimension: \emptyset 30 mm

Front form: Round

Front bezel colour: Black

Front bezel material: Plastic

MOUNTING

Design: Raised

Mounting cut-out: Ø 22.3 mm

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lever colour: White

Lever bar colour: White

Lever material: plastic

Lever shape: short

ELECTRICAL CHARACTERISTICS

Protection class:

MECHANICAL CHARACTERISTICS

Switching action: Momentary - Rest - Momentary

Switching positions: 3 positions

Switching angle: 45° left / 45° right

Mechanical lifetime: 1 Mil. cycles of operation

Tightening torque: 2 ... 3 Nm (17.7 ... 26.6 Lb-in)

Weight: 0.027 kg

AMBIENT CONDITION

IP front protection: IP65

IK front protection: IK03

Operating temperature: $-25 \, ^{\circ}\text{C} \, ... + 55 \, ^{\circ}\text{C}$

Shock resistance: 30g, 18ms (EN-IEC 60068-2-27)

Vibration resistance: 5g f= 2...500Hz (EN-IEC 60068-2-6)

Climate resistance: +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)

CERTIFICATE

Conformities: CE

REACH: REACH compliant

RoHS: RoHS compliant

Standards: CSA C22-2, IEC EN 60947-1, IEC EN 60947-5-1, UL508

OTHER

Short Description: Actuator, Ø 22.3 mm, Ø 30 mm, illuminative, White, short, Round, Black, Plastic,

Momentary - Rest - Momentary, IP65, IK03


Housing colour: Black

Housing material: Plastic


max. number of switching

elements:

Switching positions:



Mounting cut-outs:



Dimension drawings:

