

# Connection module

46-581.1800

Distribution by Newark



<https://newark.eao.com/component/46-581.1800/...>

Your product:

---



## 46-581.1800 Connection module

*Loading ...*

### FRONT

<b>Front form:</b>	Round
<b>Colour:</b>	Grey

### MOUNTING

<b>Mounting type:</b>	Panel mounting
-----------------------	----------------

### ELECTRICAL CHARACTERISTICS

<b>Rated insulation voltage Ui:</b>	Ui 690V - Uimp 4KV (IEC-EN60947-1)
<b>Pollution degree:</b>	3
<b>Protection class:</b>	II, according to EN / IEC 61140

### MECHANICAL CHARACTERISTICS

<b>Weight:</b>	0.165 kg
----------------	----------

### AMBIENT CONDITION

<b>IP front protection:</b>	IP44
<b>IK front protection:</b>	IK07
<b>Operating temperature:</b>	- 25 °C ... + 65 °C

### CERTIFICATE

<b>Conformities:</b>	CE
<b>REACH:</b>	REACH compliant

**RoHS:** RoHS compliant

**Standards:** IEC EN 60947-1, IEC EN 60947-5-1

**OTHER**

**Short Description:** Connection module, Round, IP44, IK07

**Material:** Plastic

**Colour RAL:** 7016 RAL